

C-2PE: Ordering Code and Specifications Table

Type Code	Displacement (cm³)	Rotation	Version	Sealing	Mounting Flange	Shaft	Flow	Inlet Fitting
C-2PE	12,18,25,32, 40,50,63,80, 108,130	Right, Left (CW, CCW)	Special Classic (S,C)	Nitrile, Viton (N,V)	According the Specifica- tions	According the Specifica- tions	S, B (Super, Bidirectional)	A (Included with Bi-directional End Cover)

	12	18	25	32	40	50	63	80	108	130	
SB2	●	●	●	●	●						SAE B-2 Hole
SB4	●	●	●	●	●	●	●				SAE B-4 Hole
SC4						●	●	●	●	●	SAE C-4 Hole

	12	18	25	32	40	50	63	80	108	130	
B13	●	●	●	●	●	●	●				SAE B 13T 16/32 "
BB15				●	●	●	●				SAE BB 15T 16/32 "
C14						●	●	●	●	●	SAE C 14T 12/24 "
D13								●	●	●	SAE D 13T 8/16 "
K1	●	●	●	●	●	●	●				1" Parallel Keyed
K1114				●	●	●	●	●	●	●	1 1/4" Parallel Keyed

ISO1179, SAE J1926, ISO6149

*Available on Request

Bi-directional Rear				
	IN	OUT		
12	G3/4, SAE 12	G3/4, SAE 12		
18	G3/4, SAE 12	G3/4, SAE 12		
25	G3/4, SAE 12	G3/4, SAE 12		
32	G1, SAE 16	G1, SAE 16		
40	G1, SAE 16	G1, SAE 16		
50	G1, SAE 16	G1, SAE 16	B02	
63	G1, SAE 16	G1, SAE 16	IN	OUT
80	G1, SAE 16	G1, SAE 16	G1 1/4, SAE 20	G1 1/4, SAE 20
108	G1, SAE 16	G1, SAE 16	G1 1/4, SAE 20	G1 1/4, SAE 20
130	G1, SAE 16	G1, SAE 16	G1 1/4, SAE 20	G1 1/4, SAE 20

	Super Rear				
	IN	OUT			
12	G3/4, SAE 12	G3/4, SAE 12			
18	G1, SAE 16	G1/2, SAE 8			
25	G1, SAE 16	G3/4, SAE 12			
32	G1 1/4 SAE 20	G3/4, SAE 12			
40	G1 1/4 SAE 20	G3/4, SAE 12			
50	G1 1/4 SAE 20	G3/4, SAE 12		S02	
63	G1 1/4 SAE 20	G3/4, SAE 12			
80	G1 1/2 SAE 24	G1, SAE 16			IN
108	G1 1/2 SAE 24	G1, SAE 16	G1 1/4, SAE 20		G1 1/4, SAE 16
130	G1 1/2 SAE 24	G1, SAE 16	G1 1/4, SAE 20		G1 1/4, SAE 16