

C-2PS: Ordering Code and Specifications Table

Type Code	Displacement (cm³)	Rotation	Version	Sealing	End Cover	Mounting Flange	Shaft
C-2PS	12,18,25,32, 40,50,63	R, L (CW, CCW)	Special Classic (S,C)	Nitrile, Viton (N,V)	Rear, Rear Suction & Rear + Side Peassure (RSR)	According the Specifi-cations	According the Specifi-cations
						ISO 3019-2	
						12	18
						25	32
						40	50
						63	
						I42	ISO 4h Ø100
						I43	ISO 4h Ø125
						S1	S2
						K1	K2

S: Splined

Thread Specifications

(R)			(RSR)		
	IN	OUT		IN	OUT
12	M27x2	M27x2	12	M27x2	M27x2
18	M33x2	M27x1,5	18	M33x2	M27x1,5
25	M33x2	M27x2	25	M33x2	M27x2
32	M42x2	M27x2	32	M42x2	M27x2
40	M42x2	M27x2	40	M42x2	M27x2
50	M42x2	M27x2	50	M42x2	M27x2
63	M42x2	M27x2	63	M42x2	M27x2

Ordering Code Example;

- End cover RSR
Sae thread

ISO 6149 (1)	BSP (B)	SEA O-Ring Boss (S)
M27x2	63/4"	1 1/16" - 12 Un-2B
M33x2	61"	1 5/16" - 12 Un-2B
M27x2	M27x2	15/8" - 12 Un-2B

- High vibration resistance and 630 bar pressure limit.
- SAE Flange 3/4" 6000 PSI x 2 High pressure series Rear Ports available for 32-40 cc
- SAE Flange 1" 6000 PSI x 2 High pressure series Rear Ports available for 50-63 cc

